

WISI DY 98 A

Multiswitch, cascade



Description

EMC according to CE, class A, terr. input level max. 89 dB μ V;
With the 13V/18V, 22 KHz-control signal max. 4 inputs can be controlled.

At a glance:

- passive
- Kaskade
- 9 inputs
- 8 participants outputs

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

Technical data

SAT-IF trunk

Inputs SAT	8 pcs.
Frequency range SAT	950...2400 MHz
Insertions loss SAT	1,3...3,4 dB
Decoupling SAT -SAT	27 dB

Terrestrial trunk

Inputs TERR	1 pcs.
Frequency range TERR	5...862 MHz
Insertion loss TERR	5.5 dB
Subscriber outputs	8 pcs.
Frequency range	5...2400 MHz
Tap loss TERR	21 dB
Tap loss SAT	21...16 dB (5 dB slope)
Decoupling Subscriber - Subscriber TERR	>42 dB
Decoupling Subscriber - Subscriber SAT	>30 dB

Connectors

F-socket	26 pcs.
----------	---------

General data

Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	210x139x27 mm
cascadable with	DY 94A...98A, DY 04...08, DY 90
Control signal	14/18 V, 22 kHz, DiSEqC 2.0

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	230 x 150 x 65 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.300 kg
Shipping unit	5 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	2.24 dm ³
Gross weight shipping unit	1.3 kg
EAN	4010056137717
Article number	13771
Customs tariff number	85291095