

A-2030D-EB

The A-2030D-EB is a high cost-performance mixer power amplifier suited for broadcasting paging or background music in schools, offices, shops, factories, mosques, churches and large rooms.



Order no: A-2030D-EB 1CE
 Alternative products: A-2030DD-EB,
 A-2060DD-EB, A-2120DD-EB, A-2240DD-EB

Specifications

Power source	220 - 240 V AC, 50 / 60 Hz
Rated output	30 W
Frequency response	50 Hz - 20 kHz (± 3 dB)
Distortion	< 1 % (at 1 kHz, 1/3 rated output power)
Current consumption	EN 60065 (AC operation at 1/3 maximum output without clip)
S/N ratio	60 dB (or more)
Number of channels	1
Connectable microphones	3
Inputs	MIC 1 – 3: -60 dBV, 600 Ω , balanced, Phone Jack AUX 1, 2: -20 dBV, 10 k Ω , unbalanced, RCA Pin Jack
Outputs	Speaker: balanced (floating) / Rec out: 0 dBV, 600 Ω , unbalanced, RCA Pin Jack
Weight	4,0 kg
Dimensions (W x H x D)	420 x 100,6 x 280,3 mm
Dimensions (ϕ x D)	x 280,3 mm
Finish	ABS resin, Steel plate, black



A-2030D-EB

Appearance