

N-8600MS

IP MASTER STATION

The N-8600MS is an IP multifunctional master station employing packet audio technology. Connecting the N-8600MS to an IP network (LAN or WAN) permits hands-free or handset conversation of high sound quality to be made between the N-8600MS and intercom stations connected to the IP Intercom Exchange, or between the N-8600MS units. Besides, the N-8600MS can be used in conjunction with the Multi Interface units through a network. The Multifunctional Master Station provides LCD display, Auto-dialer function enabling one-touch dialing, headset terminal and external speaker terminal. Power can be supplied from the PoE (Power over Ethernet) switching hub. (In this case, an AC adapter is not required.) This station can be mounted to the wall using an optional YC-280 wall mounting bracket.



Article number: N-8600MS Y
Alternative products: N-8610RM

Specifications

Network	10BASE-T/100BASE-TX (Automatic-Negotiation)
Network protocol	TCP/IP, UDP, ARP, ICMP, HTTP, RTP, IGMP
Audio packet transmission system	Unicast, Multicast
Voice packet loss recovery	silence insertion
Audio delay time	80 ms, 320 ms (controllable on the software)
Frequency response	300 Hz - 7 kHz
Power source	Power supply device that complies with IEEE802.3af standard or 12 V DC (supplied from the AC Adapter (option))
Power consumption	3 W (max.)
Speech method	Hands-free or handset conversation
Dimensions (W x H x D)	148 x 208 x 70,5 mm
Dimensions (ø x D)	x 70,5 mm
Finish	ABS resin, grey,
Operating humidity	90 % RH or less (no condensation)
Operating temperature	0 °C to +40 °C

N-8600MS

IP MASTER STATION

Appearance

