



# Delegate Unit

## TS-0621A



### Feature:

- \* Unique patented technology; with anti-RF tube to prevent noise and secure a perfect conference environment.
- \* Unique patented appearance, delicate and modernize.
- \* Special microphone head design, even without cotton cover, it can also eliminate the low frequency impact sound.
- \* Professional cardioid capacitor microphone core; with high sensitivity and clear voice; with red and green annular indicator light.
- \* Red indicator light means MIC is on; green indicator light means applying for talking.
- \* With feedback function. When microphone on, built-in speaker will be off.
- \* Built-in speaker and earphone jack, earphone volume is adjustable.
- \* The unit cascade with a professional 8-core aviation plug with a metal fixed nut, which will not loosen or fall off.
- \* The unit comes with a 1.8-meter wire, and the wire is shielded by full-line aluminum foil + waterline, which greatly reduces the interference of strong electromagnetic waves on the wire to avoid noise.
- \* The address code of each unit can be adjusted freely at any time to facilitate construction.
- \* Mic units power supplied by conference controller, 24V DC, safety use.
- \* Hand in hand connection, easy for installation and maintenance.

### Specifications:

|                     |                                       |
|---------------------|---------------------------------------|
| Model               | TS-0621A                              |
| Microphone Type     | Cardioid directional electret         |
| Frequency Response  | 80Hz~16KHz                            |
| MIC input Impedance | 1K $\Omega$                           |
| Sensitivity         | -34 $\pm$ 2dB(0dB=1V/Pa,at 1kHz)      |
| Max SPL             | 100dB(THD>3%)                         |
| SNR                 | >80dB                                 |
| Crosstalk           | >70dB                                 |
| Dynamic Range       | >80dB                                 |
| THD                 | <0.1%                                 |
| Max Consumption     | 2W                                    |
| Earphone Load       | 8-32 $\Omega$                         |
| Earphone Volume     | Max 40mW                              |
| Earphone Jack       | 3.5mm Mono jack                       |
| Standard            | IEC60914                              |
| Connector           | 1.8m Aviation 8 core                  |
| Power Supply Mode   | DC24V                                 |
| Color               | Silver                                |
| Weight              | 0.9kg                                 |
| Microphone Length   | 409mm                                 |
| Dimension(mm)       | 225(L) $\times$ 131(W) $\times$ 48(H) |
| Mounting            | Desktop                               |