



Conference Delegate Unit

Embedded software: conference delegate embedded control software V1.2

TS-0223A



Feature:

- * Embedded fully digital touch control design, elegant and compact appearance, user-friendly operation.
- * Adopt the brand-new CNC design, capacitive touch buttons, no key knocking noise, long lifespan, waterproof design.
- * 48KHZ sampling rate, clear and bright sound, better than the CD sound quality, built-in DSP audio processing, no low frequency impact sound.
- * Internal feedback suppression function can effectively prevent howling.
- * Voice control function can intelligently turn on the microphone.
- * 5-band EQ adjustment function, can adjust sound effects according to the characteristics of different speakers to achieve perfect effect.
- * 100m network transmission, hand-in-hand cascade, long-distance transmission with good sound quality.

Specifications:

Model	TS-0223A
Microphone type	Cardioid directional electret
Frequency response	80Hz-16KHz
Input impedance	1K Ω
Sensitivity	-46dBV/Pa
Maximum SPL	125dB (THD>3%)
SNR	>80dB (A)
Dynamic range	>80dB
THD	<0.1%
Power consumption	1.8W
Standard	IEC60914
Connector	With 1.8m 6-pin aviation connector
Power supply	Controller power supply
Color	Gray
Sign-in	Touch button sign-in
Weight	0.5Kg
Microphone pole	409mm
Size	108×77×129mm
Installation	Embedded
Desktop opening size	65×54mm