

Security Systems

PAS100 AUTOMATIC PERSONAL PARKING BARRIER | **PAS100**

Optima PAS-100 parking space saver is a simple and automatic vehicle access control system. PAS-100 automatic parking barrier secures your personal parking area against forced and unauthorized entry. Automatic Personal Parking Barrier, an OPTIMA product, protects your private parking area when you are away. Since it is automatic, it is easy and convenient to use.



SYSTEM FEATURES

MODEL	PAS-100
Height	486 mm
Material	Carbon steel
Opening and Closing Time	3 seconds
Supply Voltage	85-265 VAC (100 mA)/12-24 VDC
Output Voltage (if needed)	12 VDC (Max2A)-24VDC(Max 1.5A)
Operating Temperature Range	(-10 °C) – (+65°C)
Communication Protocols (optional with Optima software)	GSM/ Bluetooth 4.0 Low Energy/Wifi/UART
GSM Features (optional with Optima software)	Quad-band: GSM850, GSM900, DCS1800, PCS1900 Support SIM card: 1.8V, 3V Transmitting power Max. 33dBm (2W) at GSM850 and GSM900 Max. 30dBm (1W) at DCS1800 and PCS1900 Receiving Sensitivity: < -108.5 dBm

(Continued to the next page.)

Bluetooth Features
(optional with Optima software)

Compliant with Bluetooth v4.2 BR/EDR and BLE specifications
+12 dBm transmitting power
NZIF receiver with -97 dBm sensitivity
Multi-connections in Classic BT and BLE
Simultaneous advertising and scanning

Security Data

ISO 27001

Availability

High availability with uptime of Four Nines (99.99%)

Monitoring

Instant monitoring by Prtg

Server Support

7/24 support

Lock


Internal lock on closed position when it is forced to a position with an external effect

Battery

The battery of PAS, which performs 10 moves per day, should be charged every 1 month

BODY MEASUREMENTS

SIDE AND FRONT VIEW OPENED



SIDE AND FRONT VIEW CLOSED

