

WISI DY 26

Multiswitch, stand alone & cascade



Description

Connection of up to 4 dish antennas with QUADRO feed systems; 16 SAT-ZF and 1 TERR. input; broadband return channel; F-connections

At a glance:

- passive
- Kaskade & Stand Alone
- 17 Inputs
- 8 participants outputs

Technical data

SAT-IF trunk	
Inputs SAT	16 pcs.
Frequency range SAT	950...2400 MHz
Gain SAT	0 dB
Input level area SAT	0 dB
Decoupling SAT -SAT	30 dB
Output level SAT	- dB
Insertions loss SAT	1,2...3,5 dB
Terrestrial trunk	
Inputs TERR	1 pcs.
Frequency range TERR	5...862 MHz
Insertion loss TERR	4...5,5 dB
Subscriber outputs	8 pcs.
Frequency range	5...2400 MHz
Tap loss TERR	22 dB
Tap loss SAT	21...16 dB (5 dB slope)
Decoupling Subscriber - Subscriber TERR	>42 dB
Decoupling Subscriber - Subscriber SAT	>30 dB
Connectors	
F-socket	25 pcs.
General data	
Operating voltage AC	- V
Operating voltage DC	- V DC
Power input standby	- W
Power consumption	- W
LNB supply voltage	- V
LNB electrical power supply	- A
Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	315 x 139 x 58 mm (incl. Socket)
cascadable with	DY 26
Control signal	DiSEqC 2.0

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	145 x 335 x 33 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.600 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	1.6 dm ³
Gross weight shipping unit	1.6 kg
EAN	4010056146573
Article number	14657
Customs tariff number	85291095