

WISI DM 52 2015

Two-way tap, 15 dB



Description

The DM 52 2015 is a double splitter for cable TV and satellite TV. The insertion loss is 4 dB and the tap loss is 15 dB. The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

At a glance:

- Frequency range from 5....2400 MHz
- Screening factor according to Class A
- DC-Bypass in the trunk line
- High port isolation and return loss

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 11. August 2017, 2:55 nachm.

Technical data

Frequency range	5...2400 MHz
Through loss	2,0...4,0 dB
TAP loss	15 dB
Directional attenuation	22 / 20 dB (5...40/40...2400 MHz)
Isolation	≥30 dB
Return loss	18...22 dB

Connectors

F-socket	4 pcs. (1x input, 1x run through, 2x branch)
----------	--

General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74 x 48 x 18 mm

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	36 x 32 x 19 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.060 kg
Shipping unit	200 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm ³
Gross weight shipping unit	0.06 kg
EAN	4010056166014
Article number	16601
Customs tariff number	85291095