

Technical data sheet

US 5 support

Item no. 6340962



U support in fixed lengths. Dimensions 50 x 50 mm.



St	Steel
FT	Hot-dip galvanised

Additional product text, instruction For bracket widths of 400 mm or more, or if the bracket is mounted at the end of a suspended support, we recommend the use of the spacer, type DSK 45.

Master data

Item no.	6340962
Type	US 5 100 FT
Description 1	U support
Description 2	3-sided perforated
Dimension	50x50x1000
Material	Steel
Material symbol	St
Surface	Hot-dip galvanised
Surface to DIN	DIN EN ISO 1461
Surface symbol	FT
Smallest sales unit (VG)	1,00 Piece
Weight	265,00 kg/100 pc.


Technical data sheet

US 5 support

Item no. 6340962



Technical data



Length	1.000,00 mm
Dimension L	1.000,00 mm
Dimension	50 x 50 x 2,5 mm
Breakable	<input type="checkbox"/>
Version	Single profile
Type of perforation	3 sides perforated
EPD article	<input checked="" type="checkbox"/>
Suitable for maintaining electrical function	<input checked="" type="checkbox"/>
Material thickness	2,50 mm
With tothing	<input type="checkbox"/>
Profile shape	U profile
Slot width	45,00 mm
Static value A	2,74 cm ²
Static value Iy	8,32 cm
Static value Iz	12,53 cm
Static value Wy	2,61 cm ³
Static value Wz	5,01 cm ³