

PT-110EDID

Computer Graphics Video over Twisted Pair Transmitter with EDID





The PT-110EDID is a twisted pair transmitter for computer graphics video signals. It converts a computer graphics signal into a twisted pair signal that is converted back to a computer graphics video signal when used with a compatible receiver

FEATURES

Max. Resolution - WUXGA & 1080p

HDTV Compatible

EDID Capture - Copies and stores the EDID from a display device

Sync Polarity Settings - H & V switches for improved display compatibility with the CAT 5 outputs System Range - Up to 100m (320ft). Greater distances possible depending on resolution and cable

Cable - UTP (unshielded twisted pair) or STP (shielded twisted pair) such as CAT 5

Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other

Ultra Compact Pico TOOLS $^{\text{TM}}$ - 4 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUT: 1 VGA/UXGA on a 15-pin HD connector

OUTPUT: 1 RJ-45 LINE OUTPUT connector

RESOLUTION: Up to WUXGA & 1080p

S/N RATIO: 69dB (worst case)

COUPLING: AC

POWER 12V DC, 320mA

CONSUMPTION:

INCLUDED Power supply

ACCESSORIES:

Product Dimensions $6.22cm \times 5.18cm \times 2.44cm (2.45" \times 2.04" \times 0.96") W, D, H$

Product Weight 0.1kg (0.2lbs) approx

Shipping Dimensions 17.40cm x 12.00cm x 8.60cm (6.85" x 4.72" x 3.39") W, D, H

Shipping Weight 0.4kg (1.0lbs) approx

