WISI DM 54 A 4020

Four-way tap, 20/20 dB







Description

The DM 54 A 4020 is a 4-way splitter for cable TV and satellite TV. The insertion loss is according to frequency 1.0/2...2.5 dB (5...862/862...2400 MHz) and the tab loss is 20/20 dB (5...862/862...2400 MHz). The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

At a glance:

- Frequency range from 5....2400 MHz
- Screening factor according to Class A
- DC-Bypass in the trunk line
- High port isolation and return loss

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7 Phone: +49 7233 66 - 280, Fax: -350

75223 Niefern - Oeschelbronn, Germany E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 11. August 2017, 2:55 nachm.

WISI DM 54 A 4020

Technical data	
Frequency range	52400 MHz
Through loss	1,0/22,5 dB (5862/8622400 MHz)
TAP loss	20/20 dB (5862/8622400 MHz)
Directional attenuation	≥25 dB
Isolation	≥21 dB
Return loss	1822 dB
Connectors	
F-socket	6 pcs. (1x input, 1x run through, 4x branch
General data	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74 x 58 x 18 mm

Packaging data	
Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	36 x 32 x 19 mm
Packaging volume sales unit	dm³
Gross weight sales unit	0.080 kg
Shipping unit	50 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm³
Gross weight shipping unit	0.08 kg
EAN	4010056166052
Article number	16605
Customs tariff number	85291095